Epson L300

DATASHEET











The Epson L300 is a single-function printer with integrated ink system, ideal for home offices and small offices, and features two extra bottles of black ink.

With Micro Piezo printhead technology and Epson genuine ink, you can easily print Epson-quality documents at an ultra-low-cost. In addition, the L300's 12 month (or 30,000 page) warranty and service support, provides peace of mind and help if you need it.

The purpose-built ink tank is fully integrated into the printer, so you can enjoy reliable colour printing without the mess or hassle often associated with nongenuine refills and third-party ink tank systems. The Epson-genuine ink bottles make it easy to refill the ink tank with their clear labelling and drip-free nozzle while fast print speeds of 9ppm*1 can boost office productivity.

The L300 is simple to set-up and use compared to third-party ink tank systems: simply fill with the ink supplied, turn the printer on and prime the ink system. Now the L300 is ready to print.

The L300 offers affordable printing and a low-cost per-print. Each set of high-volume ink bottles can print up to 4,000 pages in black and 6,500 pages in colour*2, delivering an ultra-low cost per page for both black and colour printing.

The L300 has a 12 percent smaller footprint than previous models*3, and easily complements any work environment it is in.

KEY FEATURES

- Purpose-built, refillable ink tank
- Ultra-low cost per page
- Hassle-free with simple set-up
- 12% smaller than previous models
- Two extra black ink bottles





PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method On-demand inkjet (Piezo electric)

Minimum Droplet Size 3 pl, With Variable-Sized Droplet Technology

Ink Technology Epson Dye Ink
Printing Resolution 5.760 x 1.440 dpi

PRINT

Draft printing speed 33 Pages/min Monochrome (plain paper 75 g/m²), 15 Pages/min Color (plain paper 75 g/m²)

Printing Speed ISO/IEC 24734 9 Pages/min Monochrome, 4,5 Pages/min Color

Colours Black, Cyan, Yellow, Magenta

For detailed information on printing speeds please visit http://www.epson.eu/testing.

PAPER / MEDIA HANDLING

Number of paper trays 1

Paper Formats A4, A5, A6, B5, C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter, 9 x 13 cm, 10 x 15 cm,

13 x 18 cm, 13 x 20 cm, 20 x 25 cm, 100 x 148 mm, 16:9

Duplex Manual

Paper Tray Capacity 100 Sheets Standard, 100 Sheets maximum, 20 Photo Sheets

Media Handling Auto Sheet Feeder

GENERAL

Energy Use 1,2 W (sleep mode), 10 W (printing), ENERGY STAR® qualified all-in-one

Product dimensions 472 x 222 x 130 (Width x Depth x Height)

Product weight 2,7 k

Noise Level 5,1 B (A) with Epson Premium Glossy Photo Paper / Photo RPM mode - 38 dB (A) with Epson

Premium Glossy Photo Paper / Photo RPM mode

Compatible Operating Mac OS 10.5.8 or later, Mac OS 10.6+, Windows 7, Windows 7 x64, Windows 8 (32/64 bit),

Systems Windows Vista, Windows Vista x64, Windows XP, Windows XP x64

OTHER

Warranty 12 months Carry in, 30.000 Pages

LOGISTICS INFORMATION

SKU	C11CC27301
Barcode	8715946523446
Dimensions Single Carton	548 x 311 x 209 mm
Carton Weight	4,12 Kg
Pallet Size Euro	40 Units (4 x 10)

Epson L300

WHAT'S IN THE BOX

- Power cable
- Setup guide
- Software (CD)
- User manual (CD)
- 4 x 70ml individual ink bottles (Bk,C,Y,M) plus 2 extra black ink bottles

INK CARTRIDGE COMPATIBILITY

T6641

T6642




T6644



INK YIELD DATA



T6641



* Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit %I INK%


















^{2. [}s2] Quoted yields/CPP are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC24712. Quoted yields/CPP are NOT based on ISO/IEC24711. Quoted yields/CPP may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature 3. [s3] Comparison made with Epson L200 integrated ink tank system



